



Mobil Super™ 1000 X2 15W-40

Mobil Passenger Vehicle Lube , French Polynesia

Everyday Protection Premium Mineral Engine Oil

Product Description

Mobil Super™ 1000 X2 15W-40 Everyday Protection is brought to you by the makers of Mobil 1. This premium mineral engine oil is designed for extended engine life to meet your most demanding vehicle maintenance needs.

Features and Benefits

- Suitable for most Japanese and Korean gasoline and diesel engines
- Proprietary Extengine Molecule technology
- Good wear protection
- Good engine cleanliness
- Good high temperature protection

Applications

Mobil Super™ 1000 Extengine products have been formulated to be suitable for use in nearly all vehicles. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 15W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.873
Total Base Number, mgKOH/g, ASTM D2896	9.9
Viscosity Index, ASTM D2270	143
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	104
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.9
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	14600
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.5

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved