



Mobil ATF™ LT 71141

Mobil Passenger Vehicle Lube , Poland

Automatic Transmission Fluid

Product Description

Mobil ATF LT71141 is a high performance ATF with long drain-performance to be applied in automatic vehicle gearboxes.

Features and Benefits

Excellent cold properties.

Balanced additive performance ensuring a smooth transmission.

Applications

Mobil ATF LT71141 is designed to meet the specific requirements of automatic transmissions.

Mobil ATF LT71141 is used for the AL4 and 4HP20 gear boxes as the automatic transmission fluid.

Specifications and Approvals

This product has the following approvals:

PSA B71 2340

Voith Turbo H55.6336.xx

ZF TE-ML 04D

ZF TE-ML 11B

ZF TE-ML 14B

ZF TE-ML 17C

MB-Approval 236.11

This product is recommended for use in applications requiring:

VW TL 52162

Properties and Specifications

Property	
Density @ 15 C, g/cm ³ , ASTM D4052	0.855
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	7.4

Property	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	37.2
Viscosity Index, ASTM D2270	168

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2023

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland Sp. zo.o.

Al. Jerozolimskie 98

00-807 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>


Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved