



## MOBIL SUPER 3000 FORMULA F 0W-30

Mobil Passenger Vehicle Lube , Poland

Fully synthetic motor oil

### Product Description

Mobil Super 3000 Formula F 0W-30 is a full synthetic motor oil developed to meet the Ford requirement "WSS-M2C950-A". It is designed to help provide long engine life and outstanding protection for diesel engines in a wide range of recently produced passenger vehicle and Light Commercial Vehicle models of Ford.

### Features and Benefits

Mobil Super 3000 Formula F 0W-30 meets the technical requirements according to Ford's standard WSS-M2C950-A, based on the OEM engine tests. The usage of this product is meant to provide the following benefits:

- Increased fuel economy<sup>1</sup>
- Extended life of diesel particulate filter<sup>2</sup>
- Enhanced lower temperature properties<sup>3</sup>

1. based on 950-A 0W-30 spec compared to the 913-D 5W-30 oil

2. based on ACEA C2 requirements

3. based on 0W-30 spec compared to 5W-30 oil

### Applications

Mobil Super 3000 Formula F 0W-30 meets the Ford requirement "WSS-M2C950-A", and can be used for diesel engines in a wide range of recently produced passenger vehicle and Light Commercial Vehicle models of Ford.

Owner's manual should be consulted for recommended viscosity grades and specification.

### Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:
ACEA A1/B1
ACEA A5/B5
ACEA C2

This product has the following approvals:
STJLR.03.5007

This product meets or exceeds the requirements of:
--

**This product meets or exceeds the requirements of:**

FORD WSS-M2C950-A

### Properties and Specifications

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	9.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	44.7
Viscosity Index, ASTM D2270	204
Density @ 15.6 C, g/ml, ASTM D4052	0.842
Pour Point, °C, ASTM D97	-42
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Ash, Sulfated, mass%, ASTM D874	0.77
Total Base Number, mgKOH/g, ASTM D2896	8
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	20613
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.96

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2021

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland sp. z o.o.

ul.Chmielna 85/87

00-805 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00


Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved