



## Mobil Super 3000 Formula FE 5W-30

Mobil Passenger Vehicle Lube , Poland

### Product Description

Mobil Super 3000 Formula FE 5W-30 is a premium quality synthetic engine oil designed to provide outstanding levels of protection and performance.

### Features and Benefits

Mobil Super 3000 Formula FE 5W-30 is industry tested so you can trust it will deliver dependable performance for your vehicle's engine.

Key features and benefits include:

- Excellent oxidation stability to reduce engine deposits and sludge build-up to keep engines running reliably
- Excellent high and low temperature properties to provide dependable protection across a wide range of driving conditions
- Enhanced low temperature capabilities for outstanding cold weather starting

### Applications

Mobil Super 3000 Formula FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans, and for anyone seeking a dependable super premium quality product.

### Specifications and Approvals

Mobil Super 3000 Formula FE 5W-30 meets or exceeds the requirements of:	
API SL	X
Ford WSS-M2C913-A	X
Ford WSS-M2C913-B	X

Mobil Super 3000 Formula FE 5W-30 is recommended by ExxonMobil for use in applications requiring:	
ILSAC GF-3	X

### Typical Properties

Mobil Super 3000 Formula FE 5W-30	
Viscosity, ASTM D 445	
cSt @ 40° C	58.6
cSt @ 100° C	10.6
Sulfated Ash, wt%, ASTM D 874	1.05
Phosphorous	0.1
Flash Point, °C, ASTM D 92	225
Density @15° C kg/l, ASTM D 4052	0.85
Pour Point, °C, ASTM D 97	-51

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland Sp. zo.o.

Al. Jerozolimskie 98

00-807 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved