



## Mobil 1™ 0W-20

Mobil Passenger Vehicle Lube , Papua New Guinea

Ultimate Full Synthetic

### Product Description

Mobil 1™ Triple Action Power+ is the ultimate full synthetic engine oil delivering outstanding engine Performance, Protection, and Cleanliness with the added benefit of Fuel Economy.

### Features and Benefits

Why these matter for your engine:

- **PERFORMANCE:** Reduces the stress of daily wear and harsh conditions for longer engine life
- **PROTECTION:** Guards against extreme temperatures to prevent breakdowns
- **CLEANLINESS:** Prevents buildup of contaminants and sludge for a cleaner engine

Mobil 1™ Triple Action Power+ is feature packed to:

- **PERFORM:** Long lasting power
- **PROTECT:** 30X\* better protection for high temperatures
- **CLEAN:** Prevents 99.9%\*\* of the harmful acid contaminants that damage your engine
- **PLUS:** Increases engine efficiency for 8.4%\*\*\* improved fuel economy

\*Based on Sequence IIIH, against API SP specification

\*\*Based on TBN, against TAN in used oil

\*\*\*Based on comparison of Sequence VIE against similar data of prior generation product recipe.

### Applications

Mobil 1™ Triple Action Power+ is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product is recommended for use in applications requiring:**

FIAT 9.55535-CR1

**This product meets or exceeds the requirements of:**

Chrysler MS-6395

**This product meets or exceeds the requirements of:**

FORD WSS-M2C962-A1

API SP Resource Conserving

API SP

API SN PLUS

API SN

API SM

ILSAC GF-6A

ACEA C5

**Properties and Specifications**

Property	
Grade	SAE 0W-20
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	13600
Pour Point, °C, ASTM D97	-48
Total Base Number, mgKOH/g, ASTM D2896	9.2
Ash, Sulfated, mass%, ASTM D874	0.76
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	45
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	8.4
Density @ 15.6 C, g/ml, ASTM D4052	0.845
Viscosity Index, ASTM D2270	163

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2023



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved