



HYDRAULIC OIL AW SERIES

Mobil Industrial , Puerto Rico

Hydraulic Oil

Product Description

Hydraulic AW Oil Series oils are good quality anti-wear hydraulic oils intended for industrial and mobile service applications, subjected to moderate operating

conditions and requiring anti-wear lubricants.

Their effective oxidation resistance and chemical stability support good oil life in moderate applications.

Features and Benefits

- Good anti-wear performance helps reduce pump wear and prolonging pump life
- Corrosion protection helps reduce the effects of moisture on system components
- Filterability to prevent filter blockage even in the presence of water

Applications

- Systems using gear, vane, radial and axial piston pumps and those containing gears and bearings where mild anti-wear characteristics are required
- Where hydraulic oil contamination or leakage is unavoidable
- Where small amounts of water are unavoidable

Specifications and Approvals

This product meets or exceeds the requirements of:	HYDRAULIC OIL AW 46	HYDRAULIC OIL AW 68
DIN 51524-2:2017-06	X	X
ISO L-HM (ISO 11158:2023)	X	X

Properties and Specifications

Property	HYDRAULIC OIL AW 46	HYDRAULIC OIL AW 68
Grade	ISO 46	ISO 68
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1A	1A
Density @ 15 C, kg/l, ASTM D1298	0.876	0.882
Emulsion, Time to 3 mL Emulsion, 54 C, min, ASTM D1401	15	20
Flash Point, Cleveland Open Cup, °C, ASTM D92	226	234
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	6.6	8.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	44	63.3

Property	HYDRAULIC OIL AW 46	HYDRAULIC OIL AW 68
Pour Point, °C, ASTM D97	-24	-18
Viscosity Index, ASTM D2270	98	98

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved