

#### Mobil Pegasus<sup>™</sup> 701 Series

Mobil Industrial , Paraguay

Gas Engine Oil

### **Product Description**

Mobil Pegasus™ 701 Series are premium natural gas engine oils formulated exclusively from specially selected base stocks of high stability. These lubricants provi excellent performance and economy for a wide variety of engine types, service severity and fuel quality.

Mobil Pegasus 701 and 701 SAE 30 are formulated with ashless dispersants, effective oxidation and corrosion inhibitors, and antiwear agents. They provide ex dispersancy, and good high-temperature stability. The formulation approach is very effective for controlling carbon and ash deposits in gas engines.

The ashless dispersants in Mobil Pegasus 701 and SAE 30 help prevent the formation of deposits that can cause detonation. Port carbon cleaning intervals in two naturally aspirated and turbocharged gas engines may be extended by using Pegasus 701 Series oils. Mobil Pegasus 701 Series has increased engine overhaul p and oil filter and spark plug life in both four-cycle and two-cycle gas engines.

### Features and Benefits

Mobil Pegasus 701 Series gas engine oils provide cleaner engines, long oil and filter life, and low lube oil consumption. The result is the potential for extended eng and reduced overhaul costs.

Features	Advantages and Potential Benefits
Good Anti-wear Properties	Lower wear of engine components Provides good break-in protection of high BMEP engines
Good Oxidation and Bulk Oil Stability	Cleaner engines Extended drain intervals Reduced filter costs Good resistance to oxidation and nitration Reduces coking and formation of undercrown deposits
Good Corrosion Resistance	Reduces valve guide wear in four-cycle gas engines Protects bearings and internal components Reduced port blockage, with longer intervals between cleaning
High Quality Basestocks	Less power loss from detonation caused by combustion chamber deposits

# **Applications**

- Crankcases and power cylinders of spark-ignited two- and four-cycle gas engines
- High speed two-cycle gas engines
- Suitable for use in modern two-cycle and four-cycle slow-speed gas engines except where severity of application requires special heavy-duty, load-caperformance
- Highly loaded 4-cycle engines requiring anti-scuff protection
- Reciprocating compressor cylinders compressing natural gas
- High output or naturally aspirated turbocharged engines operating at or in excess of rated capacity under high temperatures

## Typical Properties

Mobil Pegasus 701 Series	701	701SAE 30
SAE Grade	40	30
Viscosity, ASTM D 445		
cSt @ 40° C	132	85

Mobil Pegasus 701 Series	701	701SAE 30
cSt @ 100° C	13.5	10
Viscosity Index, ASTM D 2270	97	97
Sulfated Ash, wt%, ASTM D 874	<0.1	<0.1
TBN #, mg KOH/g, ASTM D 2896	2.2	1.7
Pour Point, °C, ASTM D 97	-15	-18
Flash Point, °C, ASTM D 92	249	238
Density @ 15° C, kg/L	0.885	0.881

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021

Autopiezas Esso Lubricantes (Distribuidor Oficial)
Avenida Madame Lynch c/ Aviadores del Chaco , Asuncion , Paraguay

(595 21) 674 900

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All promany not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intenoverride or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

