



Mobil Super™ 0W-20

Mobil Passenger Vehicle Lube , Saudi Arabia

Synthetic Motor Oil

Product Description

Mobil Super™ 0W-20 is a synthetic motor oil, which provides excellent high temperature protection even under severe operating conditions. Mobil Super™ 0W-20 is designed to help provide long engine life and outstanding protection. Mobil Super™ 0W-20 provides outstanding protection against sludge, engine rust and corrosion under severe and low-temperature operating conditions and provides optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super™ 0W-20, is classified by The American Petroleum Institute (API) as a ""Resource Conserving"" engine lubricant and meets ILSAC GF-6A and API service SP.

Features and Benefits

- Helps extend engine life
- Outstanding wear protection
- Excellent high temperature protection to help keep engines cool
- Helps control oil consumption and loss
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts

Specifications and Approvals

This product meets or exceeds the requirements of:
API SJ
API SL
API SM
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
API SP
API SP Resource Conserving
ILSAC GF-6A
Ford WSS-M2C947-A
Ford WSS-M2C947-B1
FORD WSS-M2C962-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Cold-Cranking Simulator, Apparent Viscosity @ -35 C, mPa.s, ASTM D5293	5180
Phosphorus, mass%, ASTM D4951	0.07
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	44.9
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.5
Total Base Number, mgKOH/g, ASTM D2896	7.5
Viscosity Index, ASTM D2270	170
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

APSCO

Jeddah, Saudi-Arabia

Tel: 00966-2-6081171 / Fax: 00966-2-6370966

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved