



MOBIL DELVAC MODERN™ 10W-40 FULL PROTECTION V4

Mobil Commercial Vehicle Lube , Sweden

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac Modern 10W-40 Full Protection V4 is high performance diesel engine oil with advanced synthetic technology that provides excellent lubrication to m high performance, low emissions engines used in severe applications. This engine oil is designed using high performance base oils which provide excelle temperature fluidity, high temperature viscosity retention and volatility control. The proven advanced additive system has been expertly engineered to help toward engine life and maintain the efficiency of emission reduction systems including the Diesel Particulate Filter (DPF).

Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase th stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and aftertreatment devices all require improv performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with aftertreatment devices. The advanced technology in Mobil | Modern 10W-40 Full Protection V4 delivers high performance, long drain interval capability and protection of exhaust systems including those fitted with Particulate Filters (DPF). The key benefits include:

Features	Advantages and Potential Benefits
Protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation	Provides capability for long drain intervals. Helps to protect against ring sticking.
Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection	Helps towards long engine life
Stay-in-grade shear stability. Very low volatility	Helps to reduce viscosity breakdown and oil consumption under heavy duty, temperature operating conditions
Low ash, sulfur and phosphorous levels	Helps to protect exhaust systems devices like those fitted with DPF
Good low temperature properties	Helps to improve pumpability and oil circulation

Applications

- Heavy Duty Diesel Engines including Euro V/VI Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective C<sub>x</sub> Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR).
- Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations.
- Naturally Aspirated and Turbo-Charged Diesel Powered Equipment.
- On-Highway Short-Haul and Long-Haul Trucks and Buses

Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment.

Specifications and Approvals

This product has the following approvals:
MB-Approval 228.51
MTU Oil Category 3.1

This product is recommended for use in applications requiring:

MAN M 3477

This product meets or exceeds the requirements of:

DAF Extended Drain

ACEA E6

## Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.7
Density @ 15.6 C, g/ml, ASTM D4052	0.861
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	91
Viscosity Index, ASTM D2270	153
Pour Point, °C, ASTM D97	-42
Total Base Number, mgKOH/g, ASTM D2896	11.3
Ash, Sulfated, mass%, ASTM D874	0.96
Flash Point, Cleveland Open Cup, °C, ASTM D92	227

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Sverige AB

Box 1035 (Fabriksgatan 7)

SE 405 22 Göteborg

+46 31 638200

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**

Exxon Mobil Esso XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved