



Mobil Delvac Legend™ 20W-50 Standard Defense

Mobil Commercial Vehicle Lube , Singapore

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Legend™ 20W-50 Standard Defense is a high performance, heavy duty engine oil that provide proven protection to diesel engines operating in sev and off-highway service applications. Mobil Delvac Legend 20W-50 Standard Defense is recommended by ExxonMobil for use in a wide range of heav applications and operating environments found in the trucking, construction, and agricultural industries. It is also suitable for gasoline engines.

This product is fully compatible with Mobil Delvac Super 20W-50 and can be used as a replacement of same.

Features and Benefits

The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers.
- On highway light and heavy duty trucking.
- Off highway industries including: trucking, construction, quarrying, and agriculture.
- Mixed diesel/gasoline engine fleets.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF-4
API SF
API SG

Properties and Specifications

Property	
Grade	SAE 20W-50

Property	
Total Base Number, mgKOH/g, ASTM D2896	9.1
Pour Point, °C, ASTM D97	-27
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	162
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	18.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	241
Density @ 15 C, g/ml, ASTM D1298	0.88
Ash, Sulfated, mass%, ASTM D874	1

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
ExxonMobil Asia Pacific Ltd
1 HarbourFront Place
#06-00 HarbourFront Tower One
Singapore 098633

+65 6885 8000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved