



Mobil Super Moto Synthetic Technology 10W30

Mobil Passenger Vehicle Lube , Singapore

Premium Four-Stroke Motorcycle Synthetic Technology Engine Oil

Product Description

Mobil Super Moto™ Synthetic Technology 10W-30 is high performance engine oil for modern motorcycle engines. Though developed for latest engine technology, Super Moto 10W-30 provides good protection for old technology engine too, align with motorcycle engine technology development trends led by major OEMs. I engine protection from heat-activated anti-wear molecule™ can make engine protected from the start of the engine to the high temperature conditions caused b continuous driving.

Features and Benefits

Mobil Super Moto Synthetic Technology 10W-30 combines a unique blend of high quality mineral and synthesised hydrocarbon baseoils together with an adv additive system.

Balanced quality oil and additives enables keep engine clean without corrosion, protecting engine and gearbox in one circulation system.

Hi traction of Mobil Super Moto Synthetic Technology 10W-30 prevents clutch slippage.

Instant engine protection from heat-activated anti-wear molecule.

57% more wear protection against industry standard based on Industry standard engine test Sequence IVA in API SL

Applications

Best for the modern four-stroke motorcycle engines JASO MA or JASO MA2 recommended by OEMs.

Good protection to motorcycle engines before introduction of JASO MA or JASO MA2.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SL	
JASO MA	
JASO MA2	

Properties and Specifications

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	70
Viscosity Index, ASTM D2270	139
Density @ 15 C, g/ml, ASTM D4052	0.849
Pour Point, °C, ASTM D97	-33

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	248
Ash, Sulfated, mass%, ASTM D874	0.8
Total Base Number, mgKOH/g, ASTM D2896	5.4
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	15000
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.2

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020  
ExxonMobil Asia Pacific Ltd  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633

+65 6885 8000  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved