



Mobil Super™ 3000 X1 FORMULA FE 5W-30

Mobil Passenger Vehicle Lube , Singapore  
Fully Synthetic Engine Oil

Product Description

Mobil Super™ 3000 engine oil series are synthetic and engineered to deliver outstanding protection.

Mobil Super™ 3000 x1 Formula FE 5W-30 provides long engine life with enhanced protection over a wide temperature range for many types and ages of vehicles including passenger cars, light commercial vehicles and vans.

Features and Benefits

Mobil Super™ 3000 x1 Formula FE 5W-30 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection
- Helps fuel economy (as per ACEA A5/B5)
- Suitable for use in both gasoline and diesel engine passenger cars, light commercial vehicles and vans.

Applications

Mobil Super 3000 x1 Formula FE 5W-30 is recommended if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress.

- Mobil Super 3000 x1 Formula FE 5W-30 can be used in a variety of gasoline and diesel automobiles, light trucks and vans designed for use of a low viscosity (SAE 5W-30) motor oil.
- Mobil Super 3000 x1 Formula FE 5W-30 is intended primarily to meet the requirements of Ford in all engines requiring WSS-M2C913-D/C but is also suitable for use in Jaguar & Land Rover vehicles calling for STJLR.03.5003.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
Ford WSS-M2C913-D
This product is recommended for use in applications requiring:
API CF
This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:
API SL
API SN Engine Test Requirements
Ford WSS-M2C913-C
ACEA A5/B5

Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	1.1
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, °C, ASTM D92	222
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	9.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	53
Phosphorus, mass%, ASTM D4951	0.09
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
ExxonMobil Asia Pacific Ltd  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633

+65 6885 8000  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved