



Mobil Super Moto™ Scooter Gear Oil

Mobil Passenger Vehicle Lube , Singapore

Product Description

Mobil Super Moto™ Scooter Gear Oil is a multi-grade 80W-90 gear oil suitable for Japanese scooter final gear transmissions. Its unique extreme pressure a increases oil film thickness under frequent start-stop scooter operating condition, protects your scooter gear from wear under extreme gear load and heat condition

Features and Benefits

Mobil Super Moto™ Scooter Gear Oil is an SAE 80W-90 gear lubricant formulated with extreme pressure additive technology that increases oil film thickness extreme gear pressure. This reduces gear set metal to metal contact, causing lower gear friction, lower gearbox temperature and noise.

Features	Advantages and Potential Benefits
Extreme pressure additives technology increases oil film thickness protection under gear pressure	Reduces gearbox friction, heat and noise under start-stop oper conditions
Good thermal stability and resistance to high temperature oxidation	Extended bearing life due to minimal deposits
Good low temperature lubrication during start up	Reduced wear at start-up and ease of start-up
Excellent rust and corrosion protection	Extended gear life
Compatible with typical seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

Scooter final gear transmission requiring API GL-4 level performance

Specifications and Approvals

This product is recommended for use in applications requiring:
API GL-4

Properties and Specifications

Property	
Grade	SAE 80W-90
Viscosity Index, ASTM D2270	97
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	143
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.23

Property	
Flash Point, °C, ASTM D92	253
Density @ 15 C, g/ml, ASTM D4052	0.885

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2023
ExxonMobil Asia Pacific Ltd
1 HarbourFront Place
#06-00 HarbourFront Tower One
Singapore 098633

+65 6885 8000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved