



**Mobil Delvac Synthetic ATF**  
Mobil Commercial Vehicle Lube , Thailand  
Advanced Technology Synthetic Automatic Transmission Fluid

Product Description

Mobil Delvac Synthetic ATF is a fully synthetic fluid recommended by Allison Transmission, Inc. and approved against the Allison TES-295 and TES-468 Specific The fluid is designed to meet the demanding requirements of modern heavy duty automatic transmissions - conventional as well as hybrid models. The synthetic b composition enables excellent performance even in some of the harshest of operating conditions. It offers outstanding gear shifting and power transfer perform Versus conventional ATF fluids, the inherently high viscosity index and stability of Mobil Delvac Synthetic ATF protects against thermal breakdown at high ope temperatures, while still providing outstanding performance at sub-zero temperatures.

Features and Benefits

Mobil Delvac Synthetic ATF advanced technology has demonstrated extended drain, long-term friction retention, and low-temperature capability. Further, it im overall transmission durability and cleanliness. Key features and benefits include

Features	Advantages and Potential Benefits
Enhanced, long-term frictional properties.	Helps improve overall and extends transmission efficiency, smooth shifting performance and fuel economy
Exceptional thermal and oxidation stability.	Keeps transmissions clean to extend life and performance even under some of the harshest driving conditic
Outstanding film-strength and anti-wear properties.	Significant wear reduction and long transmission life.
Excellent low-temperature fluidity.	Provides prompt and reliable lubrication at sub-zero ambient temperatures down to –54° C.
Exceptional shear stability.	Leads to viscosity retention even under the severest heavy duty, high temperature operating conditions.
Compatible with mineral ATF fluids	Reduced concern in top-off situations and excellent seal materials leakage control.

Applications

Mobil Delvac Synthetic ATF is recommended by ExxonMobil for use in modern high performance trucks, buses, utility vehicles, haulers, vans and other equi requiring Allison TES-295 and TES-468 or MB-Approval 236.91 performance levels.

Specifications and Approvals

Mobil Delvac Synthetic ATF has the following builder approvals:
Allison TES-295 (AN - 051005)
Allison TES-468 (AN – 051005)
MB-Approval 236.91
ZF TE-ML 04D/ 14C/ 16M/ 20C
Voith Turbo H55.633639
Voith Turbo DIWA Service Bulletin 013 & 118- Extended Drain

Typical Properties

Mobil Delvac Synthetic ATF	
Viscosity, ASTM D 445	
cSt @ 40° C	39
cSt @ 100° C	7.3

Mobil Delvac Synthetic ATF	
Brookfield Viscosity, ASTM D 5293	
-cP @ -40° C	8400
Viscosity Index, ASTM D 2270	168
Pour Point, °C, ASTM D 97	-54
Flash Point, °C, ASTM D 92	236
Density @15° C kg/l, ASTM D 4052	0.85
Color	Red

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022  
ExxonMobil Marketing (Thailand) Limited  
3195/26, 22nd Floor, Rama IV Road  
Klong Ton, Klong Toey District  
Bangkok 10110  
Thailand

+66 2 407 4000  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pri may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved