



Mobil Super 2000 Turbospeed 10W-30

Mobil Passenger Vehicle Lube , Thailand
Premium Synthetic-Blend Diesel Engine Oil

Product Description

Mobil Super 2000 Turbospeed 10W-30 is a high performance synthetic-blend premium motor oil that is specially designed to suit Thailand diesel powered pick ups and passenger vehicles, providing excellent performance and protection.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle.
Mobil Super 2000 Turbospeed 10W-30 is designed to protect against the damage resulting from contamination and heat experienced in tough driving conditions.

- Excellent engine cleanliness, wear protection and power performance
- Excellent protection from start-up
- Improved fuel economy
- Low oil consumption between services, reducing the need for top-up
- Greater oxidation protection to protect your turbocharged engine
- Suitable for nearly all driving conditions

Applications

Mobil Super 2000 Turbospeed 10W-30 is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Diesel engines in passenger cars, SUV’s, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines
- Stop and Go City Driving
- Off road driving where dust and mud are common
- Towing and hauling heavy loads

Always consult your owner’s manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 2000 Turbospeed 10W-30 meets or exceeds the requirements of:	
API	CI-4/SL

Typical Properties

Mobil Super 2000 Turbospeed 10W-30	
SAE Grade	
Filling	
Viscosity, ASTM D 445	
cSt @ 40°C	74

Mobil Super 2000 Turbospeed 10W-30	
cSt @ 100°C	11.5
Viscosity Index, ASTM D 2270	135
Sulfated Ash, wt%, ASTM D 874	1.3
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	220
Density @15 °C kg/l, ASTM D 4052	0.87

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020
ExxonMobil Marketing (Thailand) Limited
3195/26, 22nd Floor, Rama IV Road
Klong Ton, Klong Toey District
Bangkok 10110
Thailand

+66 2 407 4000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved