



## Mobil Delvac XHP™ Extra 10W-40

Mobil Commercial Vehicle Lube , Tunisia

Extra High Performance Diesel Engine Oil

### Product Description

Mobil Delvac XHP Extra 10W-40 is a synthetic extra high performance diesel engine oil engineered to provide outstanding lubrication to modern, high performance diesel engines used in severe on and off-highway applications. This diesel engine oil is designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control, and fuel economy improvement. These base oils are enhanced with an advanced additive system, which provides a high level of protection to all parts of the engine. Mobil Delvac XHP Extra 10W-40 is engineered to provide long oil drain intervals in modern diesel engines.

### Features and Benefits

High output, low emission engines significantly increased demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Thermal stresses on the lubricant are increased with the use of inter-coolers and turbochargers. Higher fuel injection pressure and retarded timing improve burn efficiency, but also increase engine temperatures, volatility, and soot loading of the oil. The

advanced technology in Mobil Delvac XHP Extra 10W-40 delivers exceptional performance in both modern diesel engines as well as older models. The key benefits include:

| Features  | Advantages and Potential Benefits  |
|---|--|
| Outstanding protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion. | Reduced wear and long engine life.<br>Outstanding control of high temperature deposits.                          |
| Reduced engine scuffing and bore polishing protection   | Excellent protection against ring sticking   |
| Extended TBN reserve  | Long-term deposit/wear control.<br>Extended oil drain potential.   |
| Excellent low temperature properties  | Improved pumpability and oil circulation.<br>Start-up wear protection.   |
| Stay-in-grade shear stability.<br>Low volatility.   | Helps to reduce viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions. |
| Excellent Viscosity Index   | Wide range of engine and temperature applications  |

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European and Japanese manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.

### Specifications and Approvals

This product has the following approvals:

**This product has the following approvals:**

Mack EO-M Plus

Mack EO-N

MAN M 3277

MB-Approval 228.5

MB-Approval 235.27

MTU Oil Category 3

RENAULT TRUCKS RLD-2

VOITH RETARDER Oil Class A

VOLVO VDS-3

**This product is recommended for use in applications requiring:**

API CF

RENAULT TRUCKS RLD

VOLVO VDS-2

**This product meets or exceeds the requirements of:**

API CH-4

API CI-4

ACEA E4

ACEA E7

RENAULT TRUCKS RXD

Scania LDF-3

**Properties and Specifications**

| Property                                      |            |
|---|------------|
| Grade   | SAE 10W-40 |
| Density @ 15.6 C, ASTM D4052                  | 0.868      |
| Ash, Sulfated, mass%, ASTM D874               | 1.6        |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 244        |

| Property   |      |
|--|------|
| Viscosity Index, ASTM D2270                                | 154  |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 98   |
| Total Base Number, mgKOH/g, ASTM D2896                     | 15.3 |
| Pour Point, °C, ASTM D97                                   | -42  |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 14.6 |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

ExxonMobil Tunisie

Immeuble Ennouzha 2, Rue 8301

Cité Montplaisir, BP 237

1002 Tunis Belvédère, Tunisie

+ 216 71 951 510

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved