



Mobil Delvac™ Light Commercial Vehicle T 5W-30

Mobil Commercial Vehicle Lube , Turkey

Premium Semi-Synthetic Commercial Vehicle Motor Oil

Product Description

Mobil Delvac™ Light Commercial Vehicle T 5W-30 is a semi-synthetic motor oil that provides long engine life and protection against sludge & wear.

Features and Benefits

Mobil Delvac™ Light Commercial Vehicle T 5W-30 is industry proven so you can trust you will get the performance you want from your vehicle. Mobil Delvac™ Light Commercial Vehicle T 5W-30 provides:

- Excellent sludge prevention
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent wear protection
- Good cold start-up performance

Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle T 5W-30 for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions
-

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Standard oil drain up to 15.000km/1 year

Specifications and Approvals

Mobil Delvac™ Light Commercial Vehicle T 5W-30 has the following builder approvals:	5W-30
VW 501 01/505 00	X

Typical Properties

Mobil Delvac™ Light Commercial Vehicle T 5W-30	
Viscosity	5W-30
/s @ 40°C ² mm	70.8

/s @ 100°C ² mm	11.9
Sulfated Ash, wt%, ASTM D 874	1.03
Phosphorous wt%, ASTM D4951	0.105
Flash Point, °C, ASTM D 92	224
Density @15° C kg/l, ASTM D 4052	0.86
Pour Point, °C, ASTM D 97	-33

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries

05-2020

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 0 216 468 96 96

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved