



## Mobil Super™ 3000 Formula VC 0W-30

Mobil Passenger Vehicle Lube , Turkey

High performance motor oil

### Product Description

Mobil Super™ 3000 Formula VC 0W-30 is a high performance motor oil approved according Volvo Car Corporation specification Motor Oil Volvo VCC 95200377.

### Features and Benefits

- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine start.

### Applications

Mobil Super 3000 Formula VC 0W-30 to be used for the 5-cyl gasoline and diesel engines requiring the Volvo VCC 95200377 specification.

Owner's manual should be consulted for recommended viscosity grades and specification.

### Specifications and Approvals

#### This product has the following builder approvals:

VOLVO 95200377

#### This product is recommended by ExxonMobil for use in applications requiring:

API SL

ACEA A5/B5

### Properties and Specifications

Property	
Grade	SAE 0W-30
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.12
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	53.6
Viscosity Index, ASTM D2270	180
Density @ 60 F, kg/m <sup>3</sup> , ASTM D4052	0.84
Pour Point, °C, ASTM D97	-42
Flash Point, °C, ASTM D92	230

Property	
Ash, Sulfated, mass%, ASTM D874	1.1
Phosphorus, mass%, ASTM D4951	0.1

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

03-2021

Mobil Oil Türk A.S.

Pakpen Plaza Halk Sokak No: 40-44 34734 Kozyatagi Istanbul

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobiloil.com.tr/tr-tr/contact-us>

Tel: +90 0 216 468 96 96

<http://www.mobiloil.com.tr>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved