



MOBIL SUPER MOTO™ FULL SYNTHETIC 5W-40

Mobil Passenger Vehicle Lube , Taiwan

Full Synthetic Motorcycle Engine Oils

Product Description

MOBIL SUPER MOTO™ FULL SYNTHETIC 5W-40 is a high performance four-stroke scooter engine oils primarily intended for general use in all types of driving.

Features and Benefits

- MOBIL SUPER MOTO™ FULL SYNTHETIC 5W-40 is a fully synthetic oil with an advanced additive system to provide excellent wear, cleanliness, and corrosion protection.
- Instant engine protection from heat-activated anti-wear molecule™ can make engine protected from the start of the engine to the high temperature conditions caused by long, continuous driving.
- MOBIL SUPER MOTO™ FULL SYNTHETIC 5W-40 is especially formulated for scooters to shield critical engine parts.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
JASO MA
JASO MA2

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.8
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.7
Density @ 15 C, g/ml, ASTM D4052	0.854
Total Base Number, mgKOH/g, ASTM D2896	10.1
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	83
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	28300
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021


ExxonMobil international Holding Inc. Taiwan Branch
6F, No 2, Section 1, Tun Hua South Road
Taipei Taiwan

+886 2 2734 6888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved