



Mobil Formula S2 10W40

Mobil Passenger Vehicle Lube , Taiwan

Product Description

Mobil™ Formula S2 10W-40 is a premium synthetic engine oil, formulated to provide engine protection beyond that of conventional engine oils.

Features and Benefits

Mobil™ Formula S2 10W-40 is formulated to provide engine protection beyond that of conventional engine oils.

- Outstanding wear protection
- Excellent engine cleanliness
- High temperature protection

Applications

Mobil™ Formula S2 10W-40 is suitable for use in gasoline, LPG and light to medium diesel powered vehicles. It is ideally suited for normal to occasionally severe operating conditions, highway cruising and some high performance applications.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SP
ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Total Base Number, mgKOH/g, ASTM D2896	11
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	102
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.7
Density @ 15.6 C, g/ml, ASTM D4052	0.865
Viscosity Index, ASTM D2270	149
Pour Point, °C, ASTM D97	-36
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	23000

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024  
ExxonMobil international Holding Inc. Taiwan Branch  
6F, No 2, Section 1, Tun Hua South Road  
Taipei Taiwan

+886 2 2734 6888  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved