



Mobil Delvac™ Light Commercial Vehicle 10W-40

Mobil Commercial Vehicle Lube , Ukraine

Superior Engine Protection Light Commercial Vehicle Oil

Product Description

Mobil Delvac™ Light Commercial Vehicle 10W-40 is an engine oil that provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European, Russian and American engines for use in a wide range of traditional light-duty commercial vehicles.

Mobil Delvac Light Commercial Vehicle 10W-40 is engineered with a blend of advanced technology base stocks and additive system to provide a strong foundation for oxidation resistance, soot handling, and wear control supplemented with excellent piston deposit protection and reduced sludge formation to help provide long engine life.

Features and Benefits

Mobil Delvac Light Commercial Vehicle 10W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. Key benefits include:

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Help to reduced sludge build-up, deposits, and long oil and engine life
Enhanced wear protection	Helps towards long component and engine life
Improved corrosion protection	Helps to reduce bearing wear to assist with long drain intervals in modern diesel engines
Advanced piston deposit control	Helps to keep engines clean with reduced maintenance costs and long engine life
Advanced soot handling to control viscosity increase, sludge build up, and filter pressure	Helps to enhance engine protection for long engine life
Enhanced low temperature pumpability	Fast start up with reduced wear operating in low temperature climates

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European, Russian, and American manufacturers
- On-highway light trucking including mixed fleets with gasoline engines.
- For GAZ Light Duty Vehicles with diesel or petrol engines requiring API CI-4 or API SL motor oils

Specifications and Approvals

This product has the following approvals:
Cummins CES 20078

This product has the following approvals:

Cummins CES 20077

DTFR 15B110

This product has the following builder approvals:

AVTODISEL (YaMZ) YaMZ-6-12

This product is recommended by ExxonMobil for use in applications requiring:

ACEA B2-98 Issue 2

ACEA A2-96 Issue 3

API CG-4

API CF-4

API CF

CUMMINS CES 20072

CUMMINS CES 20071

This product meets or exceeds the requirements of the following industry specification:

API CI-4

API CH-4

API SL

API SJ

CUMMINS CES 20076

This product meets or exceeds the requirements of:

ACEA E7

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	100

Property	
Viscosity Index, ASTM D2270	154
Ash, Sulfated, mass%, ASTM D874	1.2
Total Base Number, mgKOH/g, ASTM D2896	11.1
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Density @ 15 C, g/ml, ASTM D1298	0.868

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>


All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved