



Mobil Delvac 1330, 1340, 1350

Mobil Commercial Vehicle Lube , United States

High Performance Diesel Engine Oils

Product Description

DISCONTINUED - The recommended replacement products are Mobil Delvac 1600 Monogrades.

Mobil Delvac 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-high conditions. Mobil Delvac 1300 monogrades are used in a wide range of applications where monograde lubricant is recommended.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against rust and sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

Applications

- Naturally aspirated and turbo-charged diesel powered equipment
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

Mobil Delvac 1300 Monogrades meet the following industry and builder specifications:	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
API CF	X	X	X
Mobil Delvac 1300 Monogrades are recommended for use in applications requiring:	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
API SF	X	X	X
Allison C-4	X		
MTU Type 2	X	X	

Typical Properties

Mobil Delvac 1300 Monogrades	Mobil Delvac 1330	Mobil Delvac 1340	Mobil Delvac 1350
SAE Grade	30	40	50
Viscosity, ASTM D 445			
cSt @ 40°C	90	132	202
cSt @ 100°C	11.5	14.7	19.5
Viscosity Index, ASTM D 2270	117	112	110
Sulfated Ash, wt%, ASTM D 874	1.4	1.4	1.4
Total Base #, mg KOH/g, ASTM D 2896	12	12	12
Pour Point, °C, ASTM D 97	-30	-21	-18
Flash Point, °C, ASTM D 92	250	256	290
Density @ 15°C kg/l, ASTM D 4052	0.889	0.892	0.896

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet.

(MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

04-2023

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved