



**Mobilarma 200 Series**  
Mobil Industrial , United States  
Rust Preventives

**Product Description**

Mobilarma 200 Series products are premium quality rust preventive materials designed to protect metal surfaces from rust and corrosion. They are formulated light-bodied petroleum solvents with polar rust preventive, water displacement and fingerprint neutralising additives. These rust preventives are easy to apply and remove making their application less man-power intensive. Mobilarma 245 is suited for the thin-film protection of finely finished parts between machining operations including operations where water-soluble cutting and grinding fluids have been used. It is also suitable for use just before parts are packaged for storage or shipment to "dry" parts as a temporary protection until a heavier rust preventive can be applied. Mobilarma 247 is the heavier duty rust preventive designed to provide long protection under more adverse conditions.

**Features and Benefits**

The Mobilarma 200 Series products provide exceptional protection of equipment during short and long-term storage. They are easy to apply and can be readily removed where necessary, prior to placing equipment back in service. They can also be used to provide a rust and corrosion protective film to equipment and component protection during shipment improving end customer satisfaction

Features	Advantages and Potential Benefits
Outstanding Rust Protection	Protects equipment and components during non-use periods Reduces need for extensive cleanup procedures prior to placing equipment back in service Reduces component replacement costs

**Applications**

- Protection of equipment during storage or while temporarily out of service
- Coating of equipment in preparation for shipment

**Properties and Specifications**

Property	245	247
Density 15.6 C, lb/gal, CALCULATED		7.05
Density @ 60 F, lb/gal, CALCULATED	6.75	
Flash Point, Cleveland Open Cup, °C, ASTM D92	38	71
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	2.6	3.0

**Health and Safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

**Exxon Mobil Corporation**  
22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil





© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved