



Mobil DTE Oil Double Letter Series

Mobil Industrial , United States

Circulating Oils

Product Description

The Mobil DTE Oil Double Letter Series of lubricants are high performance heavy duty circulating oils primarily intended for continuous reuse in circulation lubr systems for gears and bearings. They are formulated from high quality base stocks and a proprietary additive system to provide superior protection against rust, ex resistance to oxidation and thermal degradation, and a high level of protection against wear, plus excellent resistance to high temperature corrosion of soft metals possess good demulsibility that permits water and other contaminants to separate readily from the oil in the system reservoir. The Mobil DTE Oil Double Letter Ser available in two ISO viscosity grades 150 and 220.

The Mobil DTE Double Letter Series family of products provides a versatile lubricant source for a wide range of industrial equipment. They provide the users wit reliable and efficient operation in industrial circulating system applications, as well as other lubricant application methods, including hydraulic systems. Th particularly resistant to the effects of prolonged high temperature exposure and perform very well in circulating systems with short oil residence times. Mobil DTE L Letter Series oils have very good water seperability properties, which allows water to separate readily in the system reservoir. Their high level of anti-wear pro results in exceptional equipment performance that not only results in fewer breakdowns but helps improve production capacity.

This combination of benefits has Mobil DTE Oil Double Letter Series the product of choice for many users around the world, for the last several decades.

Features and Benefits

The Mobil DTE family of products is well known and highly regarded world-wide based on their outstanding performance and the RandD expertise and the technical support which stand behind the brand. The highly versatile performance of one series of oils in this family, Mobil DTE Oil Double Letter Series oils, has them the choice of many users around the world for many decades.

Mobil DTE Named oils enjoy an excellent reputation in the lubrication of the circulation systems of industrial gearboxes, plus a wide variety of ancillary equip including hydraulic systems. As designs change and increase in severity, it is the challenge of our scientists to understand the effect of these changes on the lubrica to formulate these products for the broad versatility they are recognized for.

For the Mobil DTE Oil Double Letter Series of lubricants this process has resulted in the use of a proprietary high quality base stocks for outstanding oxidation st plus a unique additive combination to ensure the excellent, wide-ranging performance of these oils. A review of the features, advantages and potential benefits product are shown below:

Features	Advantages and Potential Benefits
Excellent thermal/oxidative and chemical degradation resistance	Long lubricant charge life giving extended drain periods and reduced product replacement costs; rec filter deposits and longer filter life
Outstanding anti-wear performance	Reduced pump wear leading to longer pump life, protection of critical bearings and gearing
Protection against rust and corrosion in both the liquid and vapour phase	Enhanced system cleanliness for reduced maintenance and un-planned stoppages
Good demulsibility and avoids emulsion formation	Improved operating efficiency and lower operating costs
Multiple application capability	Reduced plant inventory savings

Applications

These oils are intended primarily for the lubrication of plain bearings, roller bearings, parallel shaft and bevel gearing. They are suitable as multipurpose lubric systems not subject to shock loading and which do not require extreme pressure performance. They are used in applications using splash, bath and ring oil arrange and all other application methods involving pumps, valves and auxiliary equipment. They are recommended for use in hydraulic systems where higher viscosity c specified.

- Moderate duty spur, bevel, helical and herringbone gear units
- Circulating systems
- Mobil DTE Oil Extra Heavy and BB can also be used in hydraulic systems employing gear, vane, radial and axial piston pumps where anti-wear hydraulic flu required and clearances are relatively large
- Certain compressors and vacuum pumps handling air, natural gas and inert gases provided the discharge temperatures do not exceed 150°C

Typical Properties

MOBIL DTE Oil Double Letter Series	Mobil DTE Oil Extra Heavy	Mobil DTE Oil BB
ISO Viscosity Grade	150	220
Viscosity, ASTM D 445		
cSt @ 40°C	146	218
cSt @ 100°C	14.4	18.8
Viscosity Index, ASTM D 2270	96	96
Pour Point, °C, ASTM D 97	-21	-18
Flash Point, °C, ASTM D 92	272	284
Density @15°C, ASTM D 1298, kg/l	0.89	0.89
Demulsibility for non-EP oils, ASTM D2711, ml free water	38	36
Water separability, ASTM D 1401, Min. to 40/37/3 ml emulsion @ 82°C	20	20
Rust Prevention, ASTM D 665		
Distilled Water	Pass	Pass
Sea Water	Pass	Pass
Copper Corrosion, ASTM D 130 hours @ 100°C	1A	1A
FZG Gear Test, DIN 51354, Failure Stage	12	12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Sawguide are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved