



MOBIL DELVAC MODERN 10W-40 FULL PROTECTION

Mobil Commercial Vehicle Lube , Uruguay

Mobil commercial-vehicle-lube

Product Description

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is an extra high performance synthetic technology diesel engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION will also deliver the same exceptional performance in older conventional engines. It meets or exceeds the requirements of the API CK-4, CJ-4 service categories as well as key Original Equipment Manufacturer (OEM) requirements.

Features and Benefits

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is formulated using synthetic technology and a detergent system to deliver excellent performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and TBN retention for long drain intervals, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

| Features | Advantages and Potential Benefits |
|---|--|
| Excellent soot-viscosity control | Helps to maintain engine efficiency, long engine life and long oil life |
| Outstanding thermal and oxidative stability | Helps to reduce low temperature sludge build-up and high temperature deposits |
| Excellent oil consumption control | Helps to lower oil costs due to less make-up oil during operation |
| Excellent TBN reserves | Helps to improve corrosion protection and to extend drain intervals |
| Stay-in-grade shear stability | Helps to maintain viscosity in severe, high temperature service for greater wear protection and long engine life |
| Excellent low temperature pumpability | Fast oil flow and helps to reduce wear during engine start-up in low temperatures |
| Excellent resistance to corrosive and abrasive wear | Long life of critical wear surfaces |
| Component compatibility | Long gasket, seal, and after treatment (DPF and DOC) life |

Applications

Recommended by ExxonMobil for use in:

- Heavy Duty Diesel Engines including Euro V/VI and China V/VI(1) modern low emissions vehicles, utilizing technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR).
- High-performance diesel applications including turbo-charged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.

Specifications and Approvals

| This product has the following approvals: | |
|--|--|
| Detroit Detroit Fluids Specification 93K222 | |
| Detroit Fluids Specification 93K218 | |
| MACK EOS-4.5 | |
| RENAULT TRUCKS RLD-3 | |
| VOLVO VDS-4.5 | |
| MAN M 3775 | |
| Ford WSS-M2C171-F1 | |
| MB-Approval 228.31 | |
| MTU Oil Category 2.1 | |

| This product is recommended for use in applications requiring: | |
|---|--|
| MAN M 3575 | |

| This product meets or exceeds the requirements of: | |
|---|--|
| API CJ-4 | |
| API CK-4 | |
| API SN | |
| ACEA E7 | |
| ACEA E9 | |
| Caterpillar ECF-3 | |
| Cummins CES 20086 | |
| Cummins CES 20081 | |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-40 |
| Viscosity Index, ASTM D2270 | 158 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10 |

| Property | |
|--|------------------|
| Pour Point, °C, ASTM D97 | -48 |
| Noack Volatility, mass%, ASTM D5800 | 10 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.11 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 219 |
| Density @ 15.6 C, g/ml, ASTM D1298 | 0.862 |
| Ash, Sulfated, mass%, ASTM D874 | 0.69 |
| Appearance, AMS 1738 | Clear and Bright |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Lidermind SA. (Distribuidor Oficial de Lubricantes ESSO)

Gral Luna N° 1370 , Montevideo, Uruguay

(598-2) 208- 6961

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved