



Mobil Delvac™ MX V2 20W-50

Mobil Commercial Vehicle Lube , Uruguay

Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ MX V2 20W-50 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

The advanced chemistry of this product provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high sulphur fuel. Mobil Delvac™ MX V2 20W-50 combines a blend of high performance base stocks with a progressive additive system to provide superior control of oil thickening due to soot build-up and high temperatures as well as outstanding resistance to oxidation, corrosion, and high temperature deposits.

Features and Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Top piston fire rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase thermal stress on the lubricant. Increased fuel injector pressure and retarded timing improve fuel burn efficiency, but also increase engine temperatures and increase soot loads. Mobil Delvac™ MX V2 20W-50 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| High thermal and oxidation stability | Reduced sludge build-up, deposits and viscosity increase |
| TBN reserves | Deposit control and acid neutralisation |
| Stay-in-grade shear stability | Wear protection and viscosity control |
| Advanced detergency/dispersancy | Cleaner engines and longer component life |
| Improved soot handling | Improved viscosity control and used oil pumpability |
| Excellent low temperature properties | Start-up wear protection |
| Component compatibility | Longer gasket and seal life |
| Meets demanding specifications of key OEMs | One engine oil for mixed fleet operations |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway light and heavy-duty trucking

- Off-highway industries including: construction, mining, quarrying, and agriculture
- Mixed fleet applications

Specifications and Approvals

This product meets or exceeds the requirements of:

API CH-4

API CI-4

Properties and Specifications

| Property | MOBIL DELVAC MX V2 20W-50 |
|----------|---------------------------|
| Grade | SAE 20W-50 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Lidermind SA. (Distribuidor Oficial de Lubricantes ESSO)

Gral Luna N° 1370 , Montevideo, Uruguay

(598-2) 208- 6961

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil ESSO XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved