



## MOBIL SUPER 3000 EURO DIESEL 5W-30

Mobil Passenger Vehicle Lube , Uruguay

Premium Full Synthetic Passenger Vehicle Engine Oil

### Product Description

Mobil Super™ 3000 Euro Diesel 5W-30 is a premium full synthetic engine oil, designed to provide outstanding levels of protection for modern vehicles in city driving. It provides outstanding engine wear protection even under the most demanding driving conditions.

### Features and Benefits

Mobil Super™ 3000 Euro Diesel 5W-30 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

### Applications

Mobil Super™ 3000 Euro Diesel 5W-30 exceeds the API SN gasoline engine oil test specification and can be used in cars that require ACEA C2/C3 specifications.

### Specifications and Approvals

<b>This product has the following approvals:</b>
--

MB-Approval 229.52
--------------------

<b>This product meets or exceeds the requirements of:</b>
---

API SN
--------

ACEA C2
---------

ACEA C3
---------

RENAULT RN0710
----------------

### Properties and Specifications

<b>Property</b>	
-----------------	--

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	168
Noack Volatility, mass%, ASTM D5800	10
Flash Point, Cleveland Open Cup, °C, ASTM D92	211
Density @ 15 C, g/ml, ASTM D4052	0.8503
Pour Point, °C, ASTM D97	-36
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.09

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2024


DISA Montevideo S.A. - San Fructuoso, 927, Montevideo - Centro Técnico (598) 22009920 interno 55175, en caso de derrames

(598) 22007185.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved