



Mobil Delvac Super 1300 15W40

Mobil Commercial Vehicle Lube , Vietnam

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1300 15W-40 is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in on and off-hi severe service applications. Mobil Delvac Super 1300 15W-40 is biodiesel compatible* and is recommended by ExxonMobil for use in a wide range of heav applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-16

Features and Benefits

The technology in Mobil Delvac Super 1300 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits includ

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:
ACEA E2
API CG-4
API CF-4
API CD
API SJ
MAN 271
VOLVO VDS

Properties and Specifications

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.2
Density @ 15.6 C, g/ml, ASTM D4052	0.88
Flash Point, °C, ASTM D92	220
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	106
Pour Point, °C, ASTM D97	-27
Total Base Number, mgKOH/g, ASTM D2896	9
Viscosity Index, ASTM D2270	136

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

Xtreme

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved