



Mobil Delvac™ Super 20W-50

Mobil Commercial Vehicle Lube , Vietnam

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 20W-50 is a high performance, heavy duty engine oil that provide proven protection to diesel engines operating in severe on and off-highway : applications. Mobil Delvac Super 20W-50 is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found trucking, construction, and agricultural industries. It is also suitable for gasoline engines.

Features and Benefits

The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On highway light and heavy duty trucking
- Off highway industries including: trucking, construction, quarrying, and agriculture
- Mixed diesel/gasoline engine fleets

Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF-4
API SF
API SG

Properties and Specifications

Property	
Grade	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	17.6
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	149

Property	
Pour Point, °C, ASTM D97	-30
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	129
Flash Point, Cleveland Open Cup, °C, ASTM D92	244
Density @ 15.6 C, g/ml, ASTM D1298	0.88

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved