



Mobil Super™ 1000 X2 15W-40

Mobil Passenger Vehicle Lube , Vietnam

Everyday Protection Premium Mineral Engine Oil

Product Description

Mobil Super™ 1000 X2 15W-40 Everyday Protection is brought to you by the makers of Mobil 1. This premium mineral engine oil is designed for extended engine meet your most demanding vehicle maintenance needs.

Features and Benefits

- Suitable for most Japanese and Korean gasoline and diesel engines
- Proprietary Extengine Molecule technology
- Good wear protection
- Good engine cleanliness
- Good high temperature protection

Applications

Mobil Super™ 1000 Extengine products have been formulated to be suitable for use in nearly all vehicles. We particularly recommend it for the following vehicle and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
VW 501 01
VW 505 00
This product is recommended for use in applications requiring:
API CF
This product meets or exceeds the requirements of:
API SJ

**This product meets or exceeds the requirements of:**

API SL

API SM

API SN

API SN PLUS

ACEA A3/B3

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.873
Total Base Number, mgKOH/g, ASTM D2896	9.9
Viscosity Index, ASTM D2270	143
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	104
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.9
Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684	14600
Pour Point, °C, ASTM D97	-39
Ash, Sulfated, mass%, ASTM D874	0.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	239
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.5

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved