



MOBIL COOLANT EXTRA READY MIXED -24°C

Mobil Ancillary, Hong Kong

超高效能冷卻液

產品說明

Mobil Coolant Extra Ready Mixed -24°C 是一款超高效能冷卻液，能在溫度低至 -24°C 的寒冷環境提供高效保護。這款產品預先混合了 36% 的 Mobil Antifreeze Extra 和 64% 的水，隨時可供使用。

應用範圍

Mobil Coolant Extra Ready Mixed -24°C 含有 BASF 的 Glysantin。BASF 研發的 Glysantin® G48® 獲以下認可：

Audi/Seat/Skoda/VW(1996 年前生產的汽車)TL 774-C、Porsche(1995 年前生產的汽車)、Rolls Royce (1998 年生產的汽車)、BMW N 600 69.0、MAN 324 NF、Mercedes-Benz specification 325 MTU MTL 5048、Opel/Vauxhall(2000 年前生產的汽車)B 040 0240、Saab 690 1599。

按照汽車製造商的建議將產品倒入汽車冷卻系統。Mobil Coolant Extra Ready Mixed -24°C 不應與含矽酸鹽的 OAT 引擎冷卻液混合使用。大部分冷卻液混合油品採用精心平衡多款防腐蝕劑的配方而成。混合冷卻液和不同的抑制劑組合可能會導致失去防蝕保護。

健康和安全

如需了解本產品的健康與安全建議，請參閱物質安全資料表 (SDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

06-2023

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai

Hong Kong

+852 3197 8888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include ExxonMobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved