



Mobil Super Moto 10W 40

Mobil Passenger Vehicle Lube , Hong Kong

優越效能四行程機車引擎機油

產品說明

Mobil™Super Moto 10W-40 是高效能、合成科技調配的四行程機車引擎機油，提供各類型四行程機車更強化的引擎清淨性及保護。

特性及效益

Mobil™Super Moto 10W-40 將優質礦物基礎油及合成碳氫基礎油獨特混和並與先進的添加劑結合，提供引擎優異的清潔、磨損保護以及有效的防止腐蝕。本優i四行程機車引擎機油提供引擎及齒輪良好保護，並使離合器運作順暢。

主要特性與效益包括:

特性	優點及潛在效益
優異的抗磨保護	較長的引擎零件及整體引擎壽命
良好的熱、氧化穩定性及積碳控制	保持運轉的引擎潔淨，使其操作順暢無誤
優異的防腐蝕性能	較長的氣門組件及軸承零件壽命
強化低溫特性	更容易低溫啟動，較長的電氣系統壽命

應用

Mobil Super Moto 10W-40 特別推薦用於需要符合最先進產業品質標準的各類四行程機車引擎潤滑。

規格與認證

本產品符合或超過以下要求：
API SL
JASO MA
JASO MA2

典型性質

Mobil Super Moto 10W-40	
SAE	10W-40
黏度, ASTM D 445	
cSt @ 40°C	100
100°C時的動黏度	14.4

Mobil Super Moto 10W-40	
黏度指數, ASTM D 2270	150
硫酸灰分, wt%, ASTM D 874	0.8
流動點, °C, ASTM D 97	-30
閃火點, °C, ASTM D 92	230
密度@ 15°C kg/l, ASTM D 4052	0.87

健康與安全

如需有關此產品的健康與安全建議，請參閱材料安全資料表 (MSDS)，其網址為：<http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有註明，此處用的商標都是埃克森美孚公司或其子公司之一的商標或註冊商標。

01-2022
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved