



Mobil Super™ 3000 Formula VC 0W-20

Mobil Passenger Vehicle Lube , Hong Kong

高性能機油

產品說明

Mobil Super™ 3000 Formula VC 0W-20 是一款高性能機油，專為滿足 Volvo 汽車公司規格機油 VCC RBS0-2AE 0W-20 而設。

特性與效益

Mobil Super 3000 Formula VC 0W-20 是一款低灰分引擎機油，其高溫高剪切 (HTHS) 黏度低於 2.75 cP。

主要特性與效益：

- 優異的低溫性能，能保證在寒冷天氣下快速發動引擎。

應用範圍

Mobil Super 3000 Formula VC 0W-20 適用於 Volvo 現代高效率汽油、柴油和混合動力車輛，以及特別要求 SAE 0W-20 黏度等級和任何機油所支援的規格之日：國車輛。

- Mobil Super 3000 Formula VC 0W-20 符合或超過 ACEA C5 行業標準，有助於提高引擎燃油效率及保護排氣後處理系統。

- 不建議將 Mobil Super 3000 Formula VC 0W-20 用於使用較高黏度引擎機油的舊款車輛引擎。

請務必參閱您的車主手冊以查看建議使用的機油黏度等級與規格。

規格與認證

本產品符合或超過以下要求：
ACEA C5

屬性和規格

屬性	
等級	SAE 0W-20
40°C 條件下的運動黏度, mm2/s, ASTM D445	41.6
100°C 條件下的運動黏度, mm2/s, ASTM D445	8.4
硫酸灰分, 質量%, ASTM D874	0.8
磷, 質量%, ASTM D4951	0.09
黏度指數, ASTM D2270	183
流動點, °C, ASTM D97	-57

屬性	
閃火點, °C, ASTM D92	230
15.6°C 條件下的密度, kg/l, ASTM D4052	0.835

健康和安全

如需了解本產品的健康與安全建議，請參閱物質安全資料表 (MSDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明，否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

04-2024
ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong
+852 3197 8888
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved