



Mobil Super™ 3000 Formula VC 0W-20

Mobil Passenger Vehicle Lube, Hong Kong

高效能機油

產品描述

美孚 Super™ 3000 Formula VC 0W-20 是一款高效能機油，專為滿足 Volvo Car Corporation (富豪汽車集團) 的 VCC RBS0-2AE 0W-20 機油等級規格要求而設。

特性與效益

美孚 Super 3000 Formula VC 0W-20 是一款低灰份引擎機油，其高溫高剪切 (HTHS) 黏度低至 2.75 cP。

主要特性與效益：

- 優異的低溫效能，即使在低溫下仍能快速啟動引擎，性能可靠。

應用範圍

美孚 Super 3000 Formula VC 0W-20 適用於 2014 年後製造，且符合 Volvo RBS0-2AE 0W-20 機油等級規格要求的四缸汽油和柴油引擎。此規格界定了 Volvo 引擎架構中柴油和汽油引擎機油的直接噴射服務應用範圍。

如需了解黏度等級和規格的建議，請參閱車主手冊

規格與認可

此產品獲得以下製造商認可：

VOLVO RBS0-2AE 0W-20

產品符合或超越以下要求：

ACEA C5

屬性和規格

屬性	
等級	SAE 0W-20
40°C 下的運動黏度, mm ² /s, ASTM D445	41.6
100°C 下的運動黏度, mm ² /s, ASTM D445	8.4
硫酸灰份, 質量%, ASTM D874	0.8
磷, 質量%, ASTM D4951	0.09
黏度指數, ASTM D2270	183

屬性	
流動點, °C, ASTM D97	-57
閃火點, °C, ASTM D92	230
15.6°C 下的密度, kg/l, ASTM D4052	0.835

健康和安全

如需了解本產品的健康與安全建議, 請參閱物質安全資料表 (MSDS): <http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有說明, 否則此處使用的所有商標均為埃克森美孚公司或其子公司的商標或註冊商標。

01-2021

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong

+852 3197 8888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved